



ROCKHARD TWO PACK CLEAR EPOXY GLOSS

IP CODE NUMBER: 750-450-004

PRODUCT DESCRIPTION

Rockhard two pack epoxy clear gloss for use where stoving is not possible or desirable. It can be used on a wide variety of substrates including metals, wood, asbestos, many synthetic rubbers and plastics. Used also as a touch up material to Rockhard stoving clear gloss 576-450-002.

APPROVALS / REFERENCES / SPECS

AFS 641; NSN 8010-98 & 8010-99; FW02651 Omat 7/162 NSN 8010-99-794-0121
Previous Reference 444/709 ; CPW approved
Used on Viper engines under DTD900 - 4492

PERFORMANCE

This product has recently undergone additional testing in preparation for acceptance to additional specifications, these tests included:

100 hours resistance to salt water fog
Resistance to engine oils and fuels
Resistance to dry heat at 180°C (355°F)

APPLICATION

Usually sprayed. Contact the technical department for advice on specific applications.

PHYSICAL PROPERTIES

Mixing Ratio	1:1 by volume with catalyst 656-450-002
Thinner	665-550-025
Supply Viscosity	Ready for use
Colour	Clear
Gloss Level	Full Gloss
Film Thickness	10 -15 Microns
Flash Point / Class / UN No	4°C / 3 / Paint UN1263
Pack Size	1 & 5 litre UN approved cans
Shelf Life	12 months