



## HEAT RESISTANT YELLOW MARKING PAINT

IP CODE NUMBER PL111R1

---

### PRODUCT DESCRIPTION

Stoving single pack, silicone / epoxy / melamine paint. Resistant to temperatures of 450°C (840°F), but will discolour after 200°C (390°F). Resistant to a wide range of chemicals, including Skydrol.

---

### APPROVALS / REFERENCES / SPECS

MSRR 9187 (re formulated July 1997); RR Code 138022; OMAT 7/110

---

### PERFORMANCE

Resistant to:

100 hours at 450°C (840°F)

Skydrol 3 hours at 70°C (160°F)

---

### APPLICATION

Spray one coat on to clean surface. Air-dry for 1 hour. For maximum protection, then stove at 190°C (375°F) for 2 hours.

Apply for RPS 661/28.

---

### PHYSICAL PROPERTIES

Mixing Ratio	One Part Product
Thinner	IP9151
Supply Viscosity	Ready for use-
Colour	Yellow - others could be made
Gloss Level	Semi gloss
Film Thickness	25 microns

Quality paints and lacquers manufactured by: Indestructible Paint Ltd  
19-25 Pentos Drive, Sparkhill, Birmingham B11 3TA. Tel:0121 702 2485; Fax 0121 778 4338

DS\CAT2\ PL & NML\PL111R1



Flash Point / Class / UN No	41°C / 3 / Paint UN1263
Pack Size	1 litre containers
Shelf Life	12 months

Quality paints and lacquers manufactured by: Indestructible Paint Ltd  
19-25 Pentos Drive, Sparkhill, Birmingham B11 3TA. Tel:0121 702 2485; Fax 0121 778 4338

DS\CAT2\ PL & NML\PL111R1