

**Indestructible Paint Ltd, 23-25 Pentos Drive, Sparkhill, Birmingham, B11 3TA, UK**

**Tel: +44 (0)121 702 2485 Fax: +44 (0)121 778 4338**

**SERMASEAL TOUCH UP COATING**



**IP Code No - PL270**

**OMAT No - 7/169A**

**Product Description -**

Inorganic touch up coating for Sermaseal 570A and IP9184 khaki Ipseal. Resistant to heat and a wide range of fuels, oils and lubricants including Skydrol.

**Approvals/References/Specs -**

RR Code 139197 OMAT 7/169A MSRR 9394

**Performance -**

Resistance to temperatures in excess of 650°C (1200°F) for 1000 hours. Resistant to Aviation fluids including Skydrol.

**Application -**

Apply to thin coat of primer IP9091 with a lint free cloth and allow to dry. Spray one coat of PL270 and allow to dry. Material is touch dry in 20 minutes but should not be subject to heat for 48 hours. Wash guns with water. Ask for RPS 661/4.

**Physical Properties -**

Mixing Ratio	One part product
Thinner	Water (Cleaning)
Supply Viscosity	Ready for use
Colour	Green / Brown
Gloss Level	Eggshell
Pack Size	500ml & 1 litre containers
Shelf Life	12 months
Health & Safety	Before use, <u>refer</u> to or <u>request</u> product Safety Data Sheet